

2018

Small -pitch HD LED display series

Fall in love with the customized internet strategy
Assist the innovative development of smart cities



Large-screen smart TV

【TV display, Glory to board】

Different HD screen 136inch/162inch

136inch/162inch	160°	1920*1080	38mm
Large size	Wide angle	Resolution	Ultrathin thickness



2K/4K Hd display picture quality

Hd standard gold display ratio is 16:9

Create the overall design of light weight and harmony


Ultrathin thickness is 38mm

High refresh makes the screen higher and clearer

The display is ultra-realistic, with a refresh rate of up to 3840hz, Professional cameras can't capture the texture of water

Display is convenient and fast

Support for adaptive display ,Multiple screens separate display



Easy operation, Let oneself free



Hardwired modularization, No wire between cabinet

Stitching is convenient

A twist, A button, wire free splice, plug and play

Product range

- Business conference complex
- Work report and product presentation
- Home theatre



Parameters

ITEM	T100	T200
Screen size :	136inch	162inch
Pixel pitch:mm	1.56	1.87
Screen resolution:	1920*1080	1920x1080
Brightness:	700	800
Scan:	Constant current	Constant current
Work environment:	indoor	indoor
Viewing angle: Cabinet	H:160 V:160°	H:160 V:160°
resolution: Waterproof	384 x 216	320 x 180
level: Average power:	IP34	IP34
W/m ² Refresh rate:Hz	225	225
Screen area:mm	≥3840	≥3840
Thickness screen:mm	3000 x 1687.5	3600 x 2025
	38	38
		150
Scene application area : m ²	100	
Attendance :	50people	100people

All series can be customized larger 4k small spacing display.

Small-pitch HD LED display series

【To light to thin very large small-pitch, design is still sexy】



To light to thin, Design is sexy, Interesting

size : 600x337.5x38mm weight :
5kg

Micro dense HD small-pitch display

P0.93mm/P1.25mm / P1.56mm /
P1.87mm / P2.3mm/P2.68mm

High IP level


Adopt all-weather protection technology IP34

- Collision protection light
- Radiation protection
- Moisture protection
- Antistatic
- Wearproof
- Efficient heat dissipation




Quick disassembling

wire free splice, plug and play



Low brightness and high grey

Color details are perfectly displayed




Small-pitch LED display

General display

(The dark level is clear) (The dark level is not clear)



16:9



	1X1	2X2	3X3	4X4	5 X5	6X6	7X7	8X8
1.25				1920x1080				3840x2160
1.56					1920x1080			
1.87						1920x1080		
2.3								

Small-pitch screen application range

- Medical system
- Command system.
- Transportation system
- Weather report
- Securities system
- Perform system.
- Network system.
- Monitoring system



Parameters

ITEM	V1.25	V1.56	V1.87	V2.3
Pixel pitch:mm	1.25	1.56	1.87	2.3
Pixel density:pix/m ²	640000	409600	284444	182044
Brightness:cd/m ²	600	700	800	900
Scan:	Constant current drive			
Work environment:	Indoor	Indoor	Indoor	Indoor
Operating temperature:	-30°C~60°C	-30°C~60°C	-30°C~60°C	-30°C~60°C
Viewing angle:	H:160 V:160°	H:160 V:160°	H:160 V:160°	H:160 V:160°
Module size:mm	150 x 168.75	150 x 168.75	150 x 168.75	150 x 168.75
Cabinet resolution:	480 x 270	386 x 216	320 x 180	256 x 144
Cabinet size:mm	600 x 337.5	600 x 337.5	600 x 337.5	600 x 337.5
Thickness Cabinet:mm	38	38	38	38
Waterproof level:	IP34	IP34	IP34	IP34
Average power: W/m ²	225	225	225	225
Refresh rate:Hz	≥3840	≥3840	≥3840	≥3840
Net weight: kg	5	5	5	5

Shenzhen TopColor Technology Co.,LTD